



UNIVERSAL SCIENTIFIC, INC.

5434S SPECIFICATIONS



5434S FEATURES:

- Liquid Crystal Display (LCD) and touch controls. Display shows remaining time in hours and minutes
- Premium top basket and 304 stainless steel bottom spindle rack with 34 spindles 8" standard. Comes with additional premium bottom basket
- Stainless Steel Triple Filtration Self-Cleaning System
- Water Temperature 82.22° C (180° F) Standard, 93° C (199° F) Optional
- Thermal and sound insulation.
- Operation at 48 decibels
- Manual-fill detergent dispenser for non-foaming powder or liquid detergent
- Manual-fill rinse aid solution dispenser
- Turbo Drying System
- Six factory-set cycle programs: DAILY, HEAVY, NORMAL, QUICK WASH, ECO, RINSE & HOLD
- Six temperature options
- End-of-program Signal
- Program memory recalls last program
- User-set delayed start (up to 24 hours)
- Seam welded tank (something we accomplish because we use high-quality steel)
- Advanced water safety system and alarm encompassing up to 16 different points to help ensure a leak-safe glassware washer

- Spring Loaded Balanced Door
- Anti-Jam, Auto-Reversing Drain Pump
- 6-foot PEX (cross-linked polyethylene) Water Line with 3/8" NPT female connection
- Nonmagnetic 18:9 high-quality stainless steel in all components that are exposed to water.
- Eight of the most important components are made of high-quality steel rather than plastic, such as: tank, loading racks, spray pipe, spray arms, filters, outer basepan, leveling legs and internal flow-thru heating element.
- 1200 watt Heating Element
- 1300 watt Max Loading
- Adjustable leveling feet
- 6-foot three prong power cord.
- One year warranty on parts and labor

MODEL REQUIREMENTS:

- Water consumption per fill 0.7 gallons
- Water flow rate 3 gallons (12 liters) per minute
- Water pressure at the washer 18-176 PSI

MODEL CONFORMS TO:

- UL
- CAN/CSA

STYLE:

Undercounter Spindle Rack

ELECTRICAL REQUIREMENTS:

120 Volts, 60 Hz, 15 Amps Duplex Receptacle

DIMENSIONS/WEIGHT:

Height (adjustable): 34 3/8" – 36"
Width: 24"
Depth: 26"
Depth (Door Open 90°): 53 1/2"
Shipping Weight: 195 lbs.

OPTIONAL ACCESSORIES:

Window in Door
Baskets and Inserts
Hold Down Screen
Water Temperature 93° C (199° F)
Customized length of spindles