



# UNIVERSAL SCIENTIFIC, INC.

## 5634ADAS SPECIFICATIONS



### 5634ADAS FEATURES:

- Hidden Control Panel w/LCD Display
- Front LED Display
- Premium Upper Rack 9" clearance and lower spindle rack with 34 customizable length 6" standard and an additional Exclusive Lower Rack 12" clearance with adjustable tines adjustable shelves
- Stainless Steel Triple Filtration Self-Cleaning System
- Water Temperature 82.22° C (180° F) Standard, 93° C (199° F) Optional
- Thermal and sound insulation.
- Operation at 48 decibels
- Manual-fill detergent dispenser for non-foaming powder or liquid detergent
- Manual-fill rinse aid solution dispenser
- Turbo Drying System
- Nine factory-set cycle programs: DAILY, HEAVY, NORMAL, DELICATE, QUICK, SUPER QUICK, ECO, RINSE & HOLD, RINSE AND DRY
- Seven temperature options
- End-of-program Signal
- Program memory recalls last program
- User-set delayed start (up to 24 hours)
- Seam welded tank (something we accomplish because we use high-quality steel

- Advanced water safety system and alarm encompassing up to 16 different points to help ensure a leak-safe glassware washer
- Spring Loaded Balanced Door
- Anti-Jam, Auto-Reversing Drain Pump
- 6-foot PEX (cross-linked polyethylene) Water Line with 3/8" NPT female connection
- Nonmagnetic 18:9 high-quality stainless steel in all components that are exposed to water.
- Eight of the most important components are made of high-quality steel rather than plastic, such as: tank, loading racks, spray pipe, spray arms, filters, outer basepan, leveling legs and internal flow-thru heating element.
- Adjustable leveling feet
- Small parts basket
- 6-foot three prong power cord.
- One year warranty on parts and labor

### MODEL REQUIREMENTS:

- Water consumption per fill 0.7 gallons
- Water flow rate 3 gallons (12 liters) per minute
- Water pressure at the washer 4.2-140 PSI

### MODEL CONFORMS TO:

- UL
- CAN/CSA

### STYLE:

American disabilities Act (ADA) Compliant Undercounter Spindle Rack

### ELECTRICAL REQUIREMENTS:

120 Volts, 60 Hz, 15 Amps Duplex Receptacle

### DIMENSIONS/WEIGHT:

Height (adjustable): 32 1/4" – 34"  
Width: 24"  
Depth: 28 7/8"  
Depth (Door Open 90°): 54 3/8"  
Shipping Weight: 185 lbs.

### OPTIONAL ACCESSORIES:

Window in Door  
Baskets and Inserts  
Hold Down Screen  
Water Temperature 93° C (199° F)